

NIGHTLINE, INC.

NIGHT VISION SPECIALISTS



IntelliVuPLUS™ Automatic Day-Night Sensor



New! IntelliVuPLUS™

System configuration enhances surveillance CCTV and zoom lenses providing Day / Night vision capability.



SYSTEM SPECIFICATIONS

| | |
|---|------------------------|
| - Magnification | Depends on Obj. Lens |
| - Focus Range | 1m to infinity |
| - Lens Requirements (C-Mount recommended) | 1" or 1/2" C/CS-Mount |
| - CCD Camera Requirements | 1/2" or 1/3" CS-Mount |
| - Light Level (from sunny day to nighttime) | 10,000 lx to 0.0001 lx |
| - Sensitivity (with f/1.4 lens) | 0.00001 fc (overcast) |
| • IMAGE INTENSIFIER | |
| - Resolution (Gamma or Delta Version) | 57 lp/mm or 64 lp/mm |
| • ELECTRICAL | |
| - Power Supply (please indicate) | 12 VDC or 24 VAC |
| • VIDEO | |
| - Signal Protocol | NTSC / PAL / SECAM |
| - Automatic Gain Control | Lens connected to CCD |
| - Iris | Auto-Iris |
| • IP-based Web Camera (OPTIONAL) | |
| - Video Standard Real Time Compression | MPEG-4 @ 30 fps |
| - Configuration | Via Web Browser |
| - PTZ support | most cameras |
| • ENVIRONMENTAL | |
| - Operating Temperature | +0° to +122°F |
| - Storage Temperature | -31° to +158°F |
| - Humidity | Up to 95% |
| • MECHANICAL | |
| - Weight (IntelliVu PLUS) | 3-1/2 lbs |
| - Dimensions (IntelliVu PLUS) | 5.1 L x 4.5 W x 4" H |